

01068575      \*\*Image available\*\*  
COMBINED CYCLE IN FUEL CELL GENERATION UNIT

PUB. NO.: 58-005975 A]  
PUBLISHED: January 13, 1983 (19830113)  
INVENTOR(s): TANAKA SUSUMU  
APPLICANT(s): TOSHIBA CORP [000307] (A Japanese Company or Corporation), JP  
(Japan)  
APPL. NO.: 56-101279 [JP 81101279]  
FILED: July 01, 1981 (19810701)  
INTL CLASS: [3] H01M-008/00  
JAPIO CLASS: 42.9 (ELECTRONICS -- Other); 35.0 (NEW ENERGY SOURCES --  
General)  
JOURNAL: Section: E, Section No. 167, Vol. 07, No. 76, Pg. 124, March  
30, 1983 (19830330)

## ABSTRACT

PURPOSE: To improve all-round efficiency of a fuel cell set by effectively using heat energy such as an exhaust on the anode- and cathode sides of the fuel cell proper and reaction heat of the fuel cell proper being emitted outside of a system of a fuel cell generation unit in a phosphate electrolyte fuel cell.

CONSTITUTION: Reaction heat generated by electrochemical reaction in a fuel cell proper 5 is absorbed by cooling water in a fuel cell cooler 23, and heated cooling water (hot water) is introduced into a steam generator 10 to be separated into steam and hot water. Hot water from the steam generator 10 is introduced into a frongas vaporizer 28 to heat frongas to be used for a frongas turbine 30 through a frongas control valve 29 to drive the frongas turbine 30 for generating electricity through a turbine generator 31. The frongas, which drove the frongas turbine 30 exchanges heat with external cooling water in a frongas condenser 32 to be recycled to the frongas vaporizer 28.

